



## CABLURI FIBRA OPTICA MULTI MODE



### PARAMETRI OPTICI AI FIBRELOR TKF MULTI-MODE MATCHED-CLADDING

Tip fibra	Diam.miez conduct.optic	Diam.acop. optica fibra	Diam. fibra invelis acrilic	Lungim de unda	Atenuare	Gigabit Perform	Largimea de banda
<b>MM 50/125</b>	50 mm	125 mm	250 mm	850 nm 1300 nm	<2,7 dB/km <0,8 dB/km	550 m 550 m	>600 MHzxkm >1200 MHzxkm
<b>MM 62,5/125</b>	62,5 mm	125 mm	250 mm	850 nm 1300 nm	<3,2 dB/km <0,9 dB/km	220 m 550 m	>200 MHzxkm >600 MHzxkm
Numar fibre / tip fibra		Diametru	Greutate	Tensiune intindere	Temperaturi	Dimensiuni role	EURO/m
<b>CTC, UNI TUBE, gel filled, metalfree, protectie ultraviolete, protectie rozatoare</b>							<b>Pret</b>
<b>CTC 1,2KN 4 x 50/125 OM2</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0,42</b>
<b>CTC 1,2KN 6 x 50/125 OM2</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0,51</b>
<b>CTC 1,2KN 8 x 50/125 OM2</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0,60</b>
<b>CTC 1,2KN 12 x 50/125 OM2</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0,76</b>
<b>CTC 1,2KN 24 x 50/125 OM2</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>1,29</b>
<b>CTC 1,2KN 4 x 62.5/125 OM1</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0,53</b>
<b>CTC 1,2KN 6 x 62.5/125 OM1</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0,67</b>
<b>CTC 1,2KN 8 x 62.5/125 OM1</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0,82</b>
<b>CTC 1,2KN 12 x 62.5/125 OM1</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>1,11</b>
<b>CTC 1,2KN 24 x 62.5/125 OM1</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>1,90</b>
<b>CTC, UNI TUBE, gel filled, metalfree, protectie rozatoare, low smoke, zero halogen</b>							<b>Pret</b>
<b>CTC 1,2KN 4 x 50/125 OM2 LSZH</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0.48</b>
<b>CTC 1,2KN 6 x 50/125 OM2 LSZH</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0.57</b>
<b>CTC 1,2KN 8 x 50/125 OM2 LSZH</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0.66</b>
<b>CTC 1,2KN 12 x 50/125 OM2 LSZH</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0.83</b>
<b>CTC 1,2KN 24 x 50/125 OM2 LSZH</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>1.34</b>
<b>CTC 1,2KN 4 x 62.5/125 OM1 LSZH</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0.66</b>
<b>CTC 1,2KN 6 x 62.5/125 OM1 LSZH</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0.78</b>
<b>CTC 1,2KN 8 x 62.5/125 OM1 LSZH</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>0.91</b>
<b>CTC 1,2KN 12 x 62.5/125 OM1 LSZH</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>1.17</b>
<b>CTC 1,2KN 24 x 62.5/125 OM1 LSZH</b>		6,8 mm	43 kg/km	1,2KN	-30 +70	4km	<b>1.95</b>
<b>CTC CS, UNI TUBE, cu armatura metalica, gel filled, metalfree, protectie rozatoare</b>							<b>Pret</b>
<b>CTC CS 1,2KN 4 x 50/125 OM2</b>		12,1 mm	142 kg/km	1,6KN	-10 +50	4km	<b>0.83</b>
<b>CTC CS 1,2KN 6 x 50/125 OM2</b>		12,1 mm	142 kg/km	1,6KN	-10 +50	4km	<b>0.90</b>
<b>CTC CS 1,2KN 8 x 50/125 OM2</b>		12,1 mm	142 kg/km	1,6KN	-10 +50	4km	<b>0.98</b>
<b>CTC CS 1,2KN 12 x 50/125 OM2</b>		12,1 mm	142 kg/km	1,6KN	-10 +50	4km	<b>1.16</b>
<b>CTC CS 1,2KN 24 x 50/125 OM2</b>		12,7 mm	162 kg/km	1,6KN	-10 +50	4km	<b>1.75</b>
<b>CTC CS 1,2KN 4 x 62.5/125 OM1</b>		12,1 mm	142 kg/km	1,6KN	-10 +50	4km	<b>0.93</b>
<b>CTC CS 1,2KN 6 x 62.5/125 OM1</b>		12,1 mm	142 kg/km	1,6KN	-10 +50	4km	<b>1.08</b>
<b>CTC CS 1,2KN 8 x 62.5/125 OM1</b>		12,1 mm	142 kg/km	1,6KN	-10 +50	4km	<b>1.19</b>
<b>CTC CS 1,2KN 12 x 62.5/125 OM1</b>		12,1 mm	142 kg/km	1,6KN	-10 +50	4km	<b>1.46</b>
<b>CTC CS 1,2KN 24 x 62.5/125 OM1</b>		12,7 mm	158 kg/km	1,6KN	-10 +50	4km	<b>2.35</b>

TOATE PRETURILE NU INCLUD TVA