



# MONDO PLAST

**cabluri si echipamente de telecomunicatii**

www.mondoplast.ro www.braungroup.ro www.cables.ro www.nextra.info

Timisoara, Str. Gloriei, 11  
tel: 0256-200.321 fax: 278.011

Bragadiru, Sos. Alexandriei, 72-74  
tel: 021-420.1310 fax: 420.0057

Mondo Plast SRL CIF: RO 12756240 capital social: 350.000 RON J11/53/2000

tel: 0256-278.000 -029 ( 30 linii)

Email : timisoara@mondoplast.net, bucuresti@mondoplast.net

## CABLURI FIBRA OPTICA SINGLE MODE



### PARAMETRI OPTICI AI FIBRELOR SINGLE-MODE MATCHED-CLADDED

Tip fibra	Diametru miez conductor optic	Diametru acoperire optica cu fibra sticla	Diametru fibra cu invelis acrilic	Lungimea de unda	Atenuare medie	Dispersie ps/(nmxkm)	Index de refractie
SM 9/125	9,3 mm	125 mm	250 mm	1310 nm	0,33 dB/km	< 3,5	1,467
				1550 nm	0,2 dB/km	< 18	1,467

Numar fibre	Diametru cablu	Greutate	Tensiune intindere	Raza min. de curbura	Temperatura de operare	Dimensiuni standard	Pret EURO/m
<b>CABLU TYPE 12 PE - Central tube, metalfree, protectie ultraviolete, protectie rozatoare</b>							
4 x 9/125	5,6 mm	23 kg/km	700 N	120mm	<b>OFERTA SPECIALA</b>		<b>0.30</b>
8 x 9/125	5,6 mm	23 kg/km	700 N	120mm	-30 +70	2000m, 4000m	<b>0.42</b>
12 x 9/125	5,6 mm	23 kg/km	700 N	120mm	-30 +70	2000m, 4000m	<b>0.51</b>
<b>CABLU TYPE 24 PE - Central tube, metalfree, protectie ultraviolete, protectie rozatoare</b>							
4 x 9/125	9 mm	66 kg/km	1400 N	135 mm	-30 +70	2000 m	<b>0.66</b>
8 x 9/125	9 mm	66 kg/km	1400 N	135 mm	-30 +70	2000 m	<b>0.78</b>
12 x 9/125	9 mm	66 kg/km	1400 N	135 mm	-30 +70	2000 m	<b>0.88</b>
24 x 9/125	9 mm	66 kg/km	1400 N	135 mm	-30 +70	2000 m	<b>1.20</b>
<b>CABLU TYPE 24 RP - Central tube, metalfree, protectie ultraviolete, protectie imbunatatita rozatoare</b>							
4 x 9/125	10,5 mm	96 kg/km	4000 N	158 mm	-30 +70	2000 m	<b>0.73</b>
8 x 9/125	10,5 mm	96 kg/km	4000 N	158 mm	-30 +70	2000 m	<b>0.84</b>
12 x 9/125	10,5 mm	96 kg/km	4000 N	158 mm	-30 +70	2000 m	<b>0.94</b>
24 x 9/125	10,5 mm	96 kg/km	4000 N	158 mm	-30 +70	2000 m	<b>1.25</b>
<b>CABLU TYPE 48 dcPE - Multi tube, metalfree, protectie ultraviolete, protectie rozatoare</b>							
6 x 9/125	10,1 mm	75 kg/km	3000 N	152mm	-30 +70	2000m, 4000m	<b>0.80</b>
12 x 9/125	10,1 mm	75 kg/km	3000 N	152mm	-30 +70	2000m, 4000m	<b>0.95</b>
24 x 9/125	10,1 mm	75 kg/km	3000 N	152mm	-30 +70	2000m, 4000m	<b>1.22</b>
36 x 9/125	10,1 mm	75 kg/km	3000 N	152mm	-30 +70	2000m, 4000m	<b>1.40</b>
48 x 9/125	10,1 mm	75 kg/km	3000 N	152mm	-30 +70	2000m, 4000m	<b>1.60</b>
<b>CABLU TYPE 48 dcPER - 4000N, Multi tube, metalfree, protectie ultraviolete, protectie rozatoare</b>							
6 x 9/125	10,1 mm	75 kg/km	4000N	152mm	-30 +70	2000m, 4000m	<b>0.91</b>
12 x 9/125	10,1 mm	75 kg/km	4000N	152mm	-30 +70	2000m, 4000m	<b>1.02</b>
24 x 9/125	10,1 mm	75 kg/km	4000N	152mm	-30 +70	2000m, 4000m	<b>1.25</b>
36 x 9/125	10,1 mm	75 kg/km	4000N	152mm	-30 +70	2000m, 4000m	<b>1.47</b>
48 x 9/125	10,1 mm	75 kg/km	4000N	152mm	-30 +70	2000m, 4000m	<b>1.69</b>
<b>CABLU TYPE 36 PE AERIAL (Figure 8) - Multi tube, 2 sufe metalice, protectie ultraviolete</b>							
6 x 9/125 Figure 8	11/20mm	195 kg/km	4800 N	165 mm	-30 +70	2000 m	<b>1.20</b>
12 x 9/125 Figure 8	11/20mm	195 kg/km	4800 N	165 mm	-30 +70	2000 m	<b>1.33</b>
24 x 9/125 Figure 8	11/20mm	195 kg/km	4800 N	165 mm	-30 +70	2000 m	<b>1.52</b>
<b>SPIRALE DE INTINDERE / SUSTINERE PT FIBRA OPTICA</b>						<b>RIBE OPTOFIT</b>	<b>EURO</b>
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic diam. 6,12-6,8mm							<b>4.7</b>
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic diam. 7,7-8,3mm							<b>6.0</b>
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic ADSS diam. 9,7-10,5mm pt deschideri <= 70m							<b>7.3</b>
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic ADSS diam. 10,51-11,36mm pt deschideri <= 70m							<b>7.3</b>
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic ADSS diam. 11,37-12,28mm pt deschideri <= 70m							<b>7.3</b>
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic ADSS diam. 12,29-13,27mm pt deschideri <= 150m							<b>7.3</b>
Intinzatoare spirala RIBE (ARMOROZI) pt cablu optic ADSS diam. 13,28-14,35mm pt deschideri <= 150m							<b>8.6</b>

TERMEN DE GARANTIE PENTRU CABLURILE OPTICE 15 ani.

PRETURILE NU INCLUD TVA